

... . . . P R O D U C T D A T A S H E E T ... . . .

## FOVAC<sup>®</sup> P3H DIRECT GREASE

### DESCRIPTION

**FOVAC<sup>®</sup> P3H Direct Grease** is a 3H NSF Rated Grease formulated as a direct contact non-toxic food grade grease with a wide temperature application in areas where food contact is unavoidable.

**FOVAC<sup>®</sup> P3H** incorporates special anti-wear and other additives that makes it suitable for all plain and anti-friction bearings as well as sliding surfaces. This product is designed for use as a Release Agent (3H) on grills, ovens, loaf pans, boning benches, chopping boards, or other hard surfaces in contact with meat and poultry food products to prevent food from adhering during processing. It is also used in meat and poultry plants, as well as all types of food processing facilities and prevents rust on hooks, trolleys and similar equipment.

**FOVAC<sup>®</sup> P3H** used to lubricate and protect food processing equipment in applications where food contact cannot be avoided. The long lasting, extreme-pressure formula is ideal for reducing stress on gears and sliding mechanisms in high load applications thus reducing the potential for expensive shutdowns.

NSF Registration Number : 168885  
 NSF-3H DIN V3 10517  
 Kosher and Parve  
 U.S Department of Agriculture Class H3  
 Halal Approved

### FEATURES

- Provides long term lubrication at wide temperatures, extending lubrication intervals
- Approved for direct contact with food
- Good sealing properties protect against the ingress of corrosive contaminants
- NSF 3H / Food Grade / Food safe for the use in HACCP Certified Food and Packaging Manufacturing Plants.
- Sliding surfaces with improved anti-wear performance prolonging component life

### APPLICATION

Bearings, Chains, Channels, Gears, conveyors, cutting blades, blending equipment, food carts, food racks, open drives, cutting blades, food extruders, filling equipment, seals, guides, ovens, grill, chopping boards, loaf pans

### SPECIFICATIONS

Operating Temperature, °C	-30 to 120
Color	White
Base Oil	Blend of white oils
NLGI Grade	1.5
Thickener	Inorganic
Shell Four Ball (IP239) Weld load, kg	400
Drop Point °C Min	None
Water Washout Test %	<5
Copper corrosion (IP 112)	Pass



### PACKING

**FOVAC<sup>®</sup> P3H** is available in 20 and 200 kg packs

Approvals By: ... . . .

*The foregoing technical information and recommendations are compiled from sources that are believed to be accurate and reliable. However, they are supplied without warranty or guarantee of any kind either expressed or implied. The purchaser is responsible for selecting and determining the suitability of products for purchaser's particular needs and we disclaim any responsibility for improper applications or misuse of our products in any manner whatsoever.*

